

UI Customization Upgrade Notes

You can customize RiskVision either by using the `ConfigureUI` option in the application UI (recommended) or manually in the `UICustomization.xml` file.

- Step 1:

UI changes done in the `ConfigureUI` feature are saved in the database. During the RiskVision upgrade, the changes are automatically handled by the upgrade code (installer). The customizations can be verified after the application is upgraded successfully.

- Step 2:

UI customization file changes are done in the `UICustomization.xml` for customizations that cannot be accomplished through `ConfigureUI`. The `UICustomization.xml` file is available in the `%AGILIANCE_HOME%\Tomcat\webapps\spc\classes` directory. To implement any changes in the `UICustomization.xml` file, you must copy the `UICustomization.xml` file to `%AGILIANCE_HOME%\config` directory and implement the customization.

If there are differences between the `UICustomization.xml` file in the backed up `%AGILIANCE_HOME%\config` directory and the `%AGILIANCE_HOME%\Tomcat\webapps\spc\classes` directory after upgrading your RiskVision server (note: changes will result from new features and other UI changes) perform the below following steps:

To implement UI Customization in the `UICustomization.xml` file

1. Copy the `UICustomization.xml` file from `%AGILIANCE_HOME%\Tomcat\webapps\spc\classes` to `%AGILIANCE_HOME%\config`.
2. Copy the changed XML blocks from the backed up `%AGILIANCE_HOME%\config` directory to the new `%AGILIANCE_HOME%\config` directory.
3. Save the `UICustomization.xml` file.