

Configuring the NVD Connector

Before the NVD connector can send any messages to the RiskVision Server, it must first be manually authenticated. Users may also wish to edit the connectors heartbeat and update settings. A description of each setting is below:

SETTING	DEFAULT VALUE	DESCRIPTION
Heartbeat period (hr:min:sec)	1 minute	Send messages, if any, and report the health of the connector.
Update period (hr:min:sec)	720 hours	Scan the file where the range is 60 and above.

To configure the connector:

1. In the **RiskVision Administration** application, click on **Administration > Connectors**.
2. Select the **NVD Connector** to open its details page.
3. Click the **Configuration** tab.
4. Click **Edit** to change the **Heartbeat period** and **Update period** as desired.



The Edit Configuration page.

5. Navigate to the **Information** tab.
6. Click **Authenticate** on the right-hand side of the screen.

Connector: NVD Connector Edit


Information

Information

Connector type NVD Connector
Name LEROY-LTP1
Description File based import connector
Version 7.5.7162.103
Domain name agilance.com
IP address(es) 192.168.237.29
Subnet mask(s) N/A

Status

Connected 
Last connected 0 sec ago
Last heartbeat N/A
Authentication  Not authenticated

 The server ignores non-authenticated connectors.

Status message
Error message No errors detected.
Queued commands 0
Feed status N/A
Last import duration N/A
Objects processed by connector N/A since import process started

The NVD Connector's details page.